

2023 CONQUEST 800 XT



GO
ANYWHERE™



GREEN



INDUSTRIAL YELLOW

HIGHLIGHTS

Engine: Versatile KX 800, liquid-cooled v-twin, 4-stroke engine with Electronic Fuel Injection (EFI)

Transmission: ODG Admiral transmission

Drive System: Instant Torque Drive System (ITDS) with Instant Torque Clutch (ITC)

Lubrication System: Auto Chain Lubrication System

Wheels & Tires: Steel Airlock™ wheels with 25" mud tires

Heavy-Duty Oil Bath Axles: Heavy-duty 1.5" forged axles in oil bath housings

Commercial Grade: Heavy-duty front brushguard and 4,500 lb. winch

2023 CONQUEST 800 XT



GO
ANYWHERE™

Engine

The versatile v-twin, 4-stroke KX engine is liquid-cooled and equipped with Electronic Fuel Injection (EFI). Capable and proven for both recreation and commercial applications, the KX delivers consistent and reliable performance in all temperatures and climates.

Auto Chain Lubrication

Designed to automatically lubricate the reinforced drive chains after timed intervals of operation, operators obtain the peace of mind they deserve while properly lubricating the machine over extended periods of time.

Transmission

The ODG admiral transmission uses a sophisticated gearing system and dual differentials located on the output shafts. The braking force is applied to a steering differential vs. to the output shafts, translating into smoother and gentler steering.

Oil Bath Axles


Axles and axle bearings can be found in an oil filled maintenance free axle housing where the Outfitter's axles stand the test of time, eliminating the need for routine maintenance.

ITDS & ITC

The ARGO Instant Torque Drive System (ITDS) delivers dramatically improved performance by coupling the trusted ARGO Instant Torque Clutch (ITC) with the bulletproof Admiral transmission to deliver increased acceleration and enhanced torque.

Alternator

Commercial grade alternator providing 60 amps of power to run auxiliary lighting and other power-hungry accessories on the job site.





ENGINE

| | |
|-------------------------|---------------|
| Cylinder | V-Twin |
| Fuel System | EFI |
| Cooling | Liquid Cooled |
| Alternator Output (max) | 60 AMPS |

DRIVETRAIN

| | |
|------------------------|------------------|
| Transmission Type | ODG Admiral |
| Drive Belt | Standard |
| Service Brakes | Hydraulic |
| Steering Brakes | Hydraulic |
| Brake Cooling Fan | Accessory |
| Auto Chain Lubrication | Standard |
| Speed on Land | 12 mph (19 Km/h) |
| Speed on Water | N/A |

DIMENSIONS/WEIGHT

| | |
|--------------------------|--------------------|
| Length | 125 in (3,175 mm) |
| Width | 65 in (1,651 mm) |
| Height | 49 in (1,245 mm) |
| Weight | 1,890 lb. (857 kg) |
| Load Capacity – Land | 1,210 lb. (549 kg) |
| Load Capacity – Water | 510 lb. (231 kg) |
| Towing Capacity | 2,000 lb. (907 kg) |
| Fuel Capacity | 8.5 gal (32 L) |
| Seating Capacity – Land | 2 |
| Seating Capacity – Water | 2 |

TIRES & WHEELS

| | |
|---------------------------|---------------------|
| ARGO Tires | ARGO XT1 19 25X12-9 |
| Wheel | Steel Airlock |
| Ground Clearance – Tires | 9 in (228 mm) |
| Ground Clearance – Tracks | 10 in (254 mm) |
| Ground Pressure - Tracks | 1.06 psi (7.3 kPa) |

FEATURES

| | |
|-------------------------|-----------|
| Front Rack | Accessory |
| Brushguard | Standard |
| Winch | 4,500 lb. |
| Full Skid Plate | Standard |
| Bilge Pump | Standard |
| Entry Step | Accessory |
| Axle Bearing Extensions | N/A |
| ROPS | Accessory |
| Rear Mesh | Accessory |
| Roof | Accessory |
| Stretcher Frame | N/A |
| Cargo Box | N/A |
| Power Dump Box | Accessory |

COLORS

| | |
|------------------|----------------------------|
| Available Colors | Green Industrial Yellow |
|------------------|----------------------------|