

LET'S GET TO WORK.



FRONTIER PRO XT

The ARGO Frontier PRO XT 6x6 delivers performance and capabilities far beyond its classification. This rugged and versatile machine offers an array of advanced safety features that set it apart from its competition, including our fully enclosed body, low center of gravity, certified Roll-Over Protection Structure (ROPS) and lap belts. With its 700 EFI fan-cooled V-Twin and its 25" mud tires, the Frontier XT 6x6 tackles challenging terrains from deep mud fields and rocky inclines to murky water crossings and unexpected natural hurdles. ARGO Progressive Steering (APS) provides precision steering capability, allowing this ground warrior to transport equipment loads and navigate any job site. Plus, its automatic chain lubrication and easy-access grease system make it quick for easy maintenance pit stops. Grab your safety hard hat, let's go.



FRONTIER PRO XT HIGHLIGHTS

- VX 700 EFI Fan Cooled V-Twin Engine
- Automatic Classic Transmission H/L/N/R
- Instant Torque Clutch
- ARGO Progressive Steering (APS)
- XT119 25x12-9 Mud Tires
- Steel Beadlock Wheels
- Heavy-Duty Front Brushguard
- 3,500 lb. Winch with Synthetic Rope
- Heavy-Duty Front Rack and Rear Rack
- Brake Cooling Fan
- Automatic Chain Lubrication System
- Easy-Access Grease System
- 2" Receiver Hitch
- 1,200 lb. Towing Capacity
- High-Density Polyethylene (HDPE) Body
- Certified Roll-Over Protection Structure (ROPS)

FRONTIER TECHNOLOGY



ENGINE

The dependable VX 700, fan-cooled, V-Twin, 4-stroke SOHC engine comes with Electronic Fuel Injection (EFI). Featuring full-pressure oil lubrication and an oil cooler to protect engine components while reducing operating temperatures, ensuring long-lasting durability and extended hours between oil changes.



TRANSMISSION

The ARGO Classic transmission operates like a mechanical skid steer that delivers incredible maneuverability while providing the ideal balance between speed and torque. Suitable for use in all types of terrain, elevations and moving heavy loads, the fully mechanical transmission is trusted to take you where others can't.



DRIVETRAIN

The ARGO Instant Torque Drive System (ITDS) delivers outstanding dramatically improved performance by coupling the trusted ARGO Instant Torque Clutch (ITC) with the bulletproof Classic transmission to deliver increased acceleration and enhanced torque.



ARGO PROGRESSIVE STEERING (APS)

Operated in conjunction with the Classic transmission, APS adds a spring element between the handlebars and the brake system to deliver a progressive, dual-rate steering system which results in an easier, smoother turning motion that instills driver confidence while offering improved steering.



FULLY ENCLOSED BODY

The one-piece, high-density polyethylene (HDPE) lower body is ARGO's signature design feature. The smooth and durable underbody allows for up to 26" of water fording while going over potential snags, stumps and outcrops delivering unparalleled stability and safe navigation.



BEADLOCK WHEELS WITH MUD TIRES

ARGO XT119 25" tires have a proprietary tread pattern for getting through thick, nasty mud and unruly terrain. The innovative ARGO beadlock rims allow for 1.5-psi tire pressure, providing a 30% smoother and more comfortable ride.



FRONTIER PRO
700 XT 8x6



AURORA PRO
800 XT 8x8



AURORA PRO
950 XT 8x8



CONQUEST PRO
800 XT 8x8



CONQUEST PRO
950 XT 8x8



CONQUEST PRO
800 XTL 8x8



CONQUEST PRO
950 XTL 8x8



CONQUEST PRO
800 XTX 8x8



CONQUEST PRO
950 XTX 8x8



MAGNUM PRO
500 XTX

ENGINE	VX 700	KX 800	VX 950	KX 800	VX 950	KX 800	VX 950	KX 800	VX 950	VX 950
CYLINDER	V-TWIN	V-TWIN	V-TWIN	V-TWIN	V-TWIN	V-TWIN	V-TWIN	V-TWIN	V-TWIN	V-TWIN
FUEL SYSTEM	EFI	EFI	EFI	EFI	EFI	EFI	EFI	EFI	EFI	EFI
COOLING	FAN COOLED	LIQUID COOLED	FAN COOLED	LIQUID COOLED	FAN COOLED	LIQUID COOLED	FAN COOLED	LIQUID COOLED	LIQUID COOLED	FAN COOLED
ALTERNATOR OUTPUT (MAX)	16 AMPS	40 AMPS	50 AMPS	60 AMPS	50 AMPS	60 AMPS	50 AMPS	60 AMPS	60 AMPS	50 AMPS
CHASSIS	6X6	8X8	8X8	8X8	8X8	8X8	8X8	8X8	8X8	8X8
SERVICE BRAKES	HYDRAULIC	HYDRAULIC	HYDRAULIC	HYDRAULIC	HYDRAULIC	HYDRAULIC	HYDRAULIC	HYDRAULIC	HYDRAULIC	HYDRAULIC
STEERING BRAKES	HYDRAULIC	HYDRAULIC	HYDRAULIC	HYDRAULIC	HYDRAULIC	HYDRAULIC	HYDRAULIC	HYDRAULIC	HYDRAULIC	HYDRAULIC
AUTO CHAIN LUBRICATION	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD
BRAKE COOLING KIT	STANDARD	STANDARD	STANDARD	N/A	N/A	N/A	N/A	N/A	N/A	N/A
TRANSMISSION	CLASSIC W/APS	ADMIRAL W/APS	ADMIRAL W/APS	ADMIRAL	ADMIRAL	ADMIRAL	ADMIRAL	ADMIRAL	ADMIRAL	ADMIRAL
DRIVE BELT	STANDARD	STANDARD	STANDARD	HEAVY DUTY	HEAVY DUTY	HEAVY DUTY	HEAVY DUTY	HEAVY DUTY	HEAVY DUTY	HEAVY DUTY
FULL SKID PLATE	HEAVY DUTY	HEAVY DUTY	HEAVY DUTY	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD
BRUSHGUARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD
WINCH	3,500 lb. w/ SYNTHETIC ROPE	3,500 lb. w/ SYNTHETIC ROPE	3,500 lb. w/ SYNTHETIC ROPE	4,500 lb. w/ SYNTHETIC ROPE	4,500 lb. w/ SYNTHETIC ROPE	4,500 lb. w/ SYNTHETIC ROPE	4,500 lb. w/ SYNTHETIC ROPE	4,500 lb. w/ SYNTHETIC ROPE	4,500 lb. w/ SYNTHETIC ROPE	4,500 lb. w/ SYNTHETIC ROPE
FRONT RACK	STANDARD	STANDARD	STANDARD	ACCESSORY	ACCESSORY	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD
REAR RACK	STANDARD	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
BILGE PUMP	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD
ROPS	STANDARD	STANDARD	STANDARD	ACCESSORY	ACCESSORY	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD
REAR MESH	N/A	N/A	N/A	ACCESSORY	ACCESSORY	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD
ROOF	N/A	STANDARD	STANDARD	ACCESSORY	ACCESSORY	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD
POWER DUMP BOX	N/A	N/A	N/A	ACCESSORY	ACCESSORY	ACCESSORY	ACCESSORY	ACCESSORY	STANDARD	STANDARD
LOAD CAPACITY - LAND	440 lb. (200 kg)	635 lb. (288 kg)	705 lb. (320 kg)	1,210 lb. (549 kg)	1,210 lb. (549 kg)	981 lb. (445 kg)	981 lb. (445 kg)	848 lb. (385 kg)	848 lb. (385 kg)	848 lb. (385 kg)
LOAD CAPACITY - WATER	240 lb. (109 kg)	435 lb. (197 kg)	505 lb. (229 kg)	510 lb. (231 kg)	510 lb. (231 kg)	281 lb. (128 kg)	281 lb. (128 kg)	148 lb. (67 kg)	148 lb. (67 kg)	148 lb. (67 kg)
TOWING CAPACITY	1,200 lb. (544 kg)	1,800 lb. (816 kg)	1,800 lb. (816 kg)	2,000 lb. (907 kg)	2,000 lb. (907 kg)	2,000 lb. (907 kg)	2,000 lb. (907 kg)	2,000 lb. (907 kg)	2,000 lb. (907 kg)	2,000 lb. (907 kg)
SEATING CAPACITY - LAND	2	4	4	2	2	2	2	2	2	2
SEATING CAPACITY - WATER	2	4	4	2	2	2	2	2	2	2
FUEL CAPACITY	8.5 gal. (32 L)	8.5 gal. (32 L)	8.5 gal. (32 L)	8.5 gal. (32 L)	8.5 gal. (32 L)	8.5 gal. (32 L)	8.5 gal. (32 L)	8.5 gal. (32 L)	8.5 gal. (32 L)	8.5 gal. (32 L)
WATER CAPABILITY	WATER FORDING	WATER FORDING	WATER FORDING	AMPHIBIOUS	AMPHIBIOUS	WATER FORDING	WATER FORDING	WATER FORDING	WATER FORDING	WATER FORDING
WEIGHT	1,100 lb. (499 kg)	1,915 lb. (869 kg)	1,845 lb. (837 kg)	1,890 lb. (857 kg)	1,890 lb. (857 kg)	2,119 lb. (961 kg)	2,119 lb. (961 kg)	2,252 lb. (1,021 kg)	2,252 lb. (1,021 kg)	2,252 lb. (1,021 kg)
LENGTH (includes winch when standard)	103 in. (2,616 mm)	126 in. (3,200 mm)	126 in. (3,200 mm)	125 in. (3,175 mm)	125 in. (3,175 mm)	125 in. (3,175 mm)	125 in. (3,175 mm)	125 in. (3,175 mm)	125 in. (3,175 mm)	125 in. (3,175 mm)
WIDTH	60 in. (1,524 mm)	60 in. (1,524 mm)	60 in. (1,524 mm)	65 in. (1,651 mm)	65 in. (1,651 mm)	65 in. (1,651 mm)	65 in. (1,651 mm)	65 in. (1,651 mm)	65 in. (1,651 mm)	65 in. (1,651 mm)
HEIGHT	77 in. (1,956 mm)	77 in. (1,956 mm)	77 in. (1,956 mm)	49 in. (1,245 mm)	49 in. (1,245 mm)	80.5 in. (2,045 mm)	80.5 in. (2,045 mm)	80.5 in. (2,045 mm)	80.5 in. (2,045 mm)	80.5 in. (2,045 mm)
AXLE BEARING EXTENSIONS	STANDARD	STANDARD	STANDARD	N/A	N/A	N/A	N/A	N/A	N/A	N/A
TIRES	ARGO XT119 25X12-9	ARGO XT119 25X12-9	ARGO XT119 25X12-9	ARGO XT117 25X12-9	ARGO XT117 25X12-9	ARGO XT119 25X12-9	ARGO XT119 25X12-9	ARGO XT119 25X12-9	ARGO XT119 25X12-9	ARGO XT119 25X12-9
WHEELS	STEEL BEADLOCK	STEEL BEADLOCK	STEEL BEADLOCK	STEEL BEADLOCK	STEEL BEADLOCK	STEEL BEADLOCK	STEEL BEADLOCK	STEEL BEADLOCK	STEEL BEADLOCK	STEEL BEADLOCK
GROUND CLEARANCE (TIRES)	10 in. (254 mm)	10 in. (254 mm)	9 in. (229 mm)	9 in. (229 mm)	9 in. (229 mm)	9 in. (229 mm)	9 in. (229 mm)	9 in. (229 mm)	9 in. (229 mm)	9 in. (229 mm)
GROUND CLEARANCE (TRACKS)	11 in. (279 mm)	11 in. (279 mm)	10 in. (254 mm)	10 in. (254 mm)	10 in. (254 mm)	10 in. (254 mm)	10 in. (254 mm)	10 in. (254 mm)	10 in. (254 mm)	10 in. (254 mm)
COLORS	YELLOW, BLACK	YELLOW, BLACK	YELLOW, BLACK	YELLOW, BLACK	YELLOW, BLACK	YELLOW, BLACK	YELLOW, BLACK	YELLOW, BLACK	YELLOW, BLACK	YELLOW, BLACK

ENGINE	443CC 4-STROKE
CYLINDER	SOHC SINGLE-CYLINDER
FUEL SYSTEM	EFI
COOLING SYSTEM	LIQUID COOLED
BORE X STROKE	89 X 71.2 mm
COMPRESSION RATIO	9.1:1
START METHOD	ELECTRIC START
TRANSMISSION TYPE	CVT AUTOMATIC
FINAL DRIVE	SHAFT DRIVE
DIFFERENTIAL FUNCTION	FRONT DIFFERENTIAL
DRIVE SYSTEM TYPE	ELECTRONIC 2WD/4WD/LOCK
ENGINE BRAKING SYSTEM (EBS)	STANDARD
LENGTH	106.3 in. (2,700 mm)
WIDTH	56.7 in. (1,440 mm)
HEIGHT	72.8 in. (1,849 mm)
GROUND CLEARANCE	10 in. (254 mm)
WHEELBASE	72 in. (1,829 mm)
TOWING CAPACITY	1,200 LB. (543 kg)
DRY WEIGHT	1,286 LB. (583 kg)
WET WEIGHT	1,332 LB. (604 kg)
FUEL TANK CAPACITY	8.5 GAL (32 l)
RIDER CAPACITY	2
SUSPENSION - FRONT & REAR	INDEPENDENT DOUBLE A-ARM
SUSPENSION TRAVEL - FRONT	6.9 in. (175 mm)
SUSPENSION TRAVEL - REAR	6.8 in. (173 mm)
BRAKE - FRONT	DUAL HYDRAULIC DISC
BRAKE - REAR	HYDRAULIC DISC
TIRE SIZE (FRONT)	AT25X8-12 (DURO)
TIRE SIZE (REAR)	AT25X10-12 (DURO)
WHEEL RIM	STEEL
ELECTRIC POWER STEERING	YES
REAR BOX STORAGE	441 LB. (200 kg)
HITCH	STANDARD/2" RECEIVER
WINCH	3,000 lb.
LIGHTING	HIGH/LOW BEAM, LED RUNNING
STORAGE	UNDER HOOD, UNDER SEAT, TAILGATE, GLOVE BOX
SPECIAL FEATURES	12V CHARGER, FRONT BRUSHGUARD, REAR BUMPER, PASSENGER HANDHOLD, 3-POINT SAFETY BELTS, SKID PLATE, HOURS METER
COLOR	YELLOW, BLACK

VISIT ARGOXTV.COM FOR THE FULL MODEL SPECS